

Feature	Specifications
Engine	18 hp Kawasaki® FR600V, 23 hp Kohler® KT730
Horsepower	18, 23
Cylinders	2
Oil Capacity	1.8 qt (1.7 L), 2 qt. (1.9 L)
Drive System	Hydro-Gear® EZT
Hydro Oil Cooler	N/A
Fuel Capacity	5 Gallon
Steering Control	Joystick
Stand-up Deck	Standard
Pivoting Front Axle	N/A
Roll-Over Protection	N/A
Tires, Rear	18x8.5-8, 18x9.5-8
Tires, Front	13x5-6
Turning Radius	Zero-Turn
Ground Speed (Forward/Reverse)	7 mph/3.75 mph
Length	79"
Height : top of seat back	43"
Height : top of ROPS extended	N/A
Height : top of ROPS folded	N/A
Width, Tractor (outside rear tires)	43", 45"
Width, Deck w/ Chute	54", 67"
Width, Deck Chute Up	43", 55"
Cutting Width	42" (2 Blades), 54"
Cutting Height	1.5" - 4.5" (1/4" increments)
Deck Construction	Welded 12 Gauge Steel Deck with 12 Gauge Strategic Reinforcements
Deck Engagement	Electric, Warner®
Blade Length	21", 18.375"
Spindle Assembly	Cast aluminum housing; 1" diameter shaft; maintenance free
Blade Tip Speed, approx.	18,000 fpm
Weight	587 lbs, 635 lbs
Seat	Adjustable molded bucket seat with sewn cover, superior wear and water resistant
Other Standard Features	Electric Start, Arm Rest, Cup Holder, Hitch Plate

Due to continuous product improvement, specifications are subject to change without notice.