

Feature	Specifications
Engine	31 hp Kawasaki® FX921V, 35 hp Kawasaki® FX1000V
Horsepower	31, 35
Cylinders	2
Oil Capacity	2 qt (1.9 L)
Drive System	Hydro-Gear® ZT-5400
Hydro Oil Cooler	Standard
Fuel Capacity	10.25 Gallon
Steering Control	Joystick, Twin Lever
Stand-up Deck	Standard
Pivoting Front Axle	Standard
Roll-Over Protection	Standard
Tires, Rear	26x12-12
Tires, Front	15x6-6
Turning Radius	Zero-Turn
Ground Speed (Forward/Reverse)	12.5 mph/7.5 mph
Length	85", 87"
Height : top of seat back	N/A
Height : top of ROPS extended	76"
Height : top of ROPS folded	49"
Width, Tractor (outside rear tires)	59"
Width, Deck w/ Chute	73", 85"
Width, Deck Chute Up	61", 73"
Cutting Width	60", 72"
Cutting Height	1.5" - 5" (1/4" increments)
Deck Construction	Laminated Welded 10 Gauge Steel Deck with 10 Gauge Reinforcement and additional 7 Gauge Spindle Mounting Reinforcement, protective bullnose front, high impact anti-scalp rollers and wear bar
Deck Engagement	Electric, Ogura®
Blade Length	21", 25"
Spindle Assembly	Cast iron housing; 1.5" diameter shaft; maintenance free & field serviceable
Blade Tip Speed, approx.	19,000 fpm
Weight	1330 lbs - 1434 lbs
Seat	Suspension Seat with 3" Adjustable Travel, Vibration Isolators, Adjustable Seat Back Recline, Adjustable Lumbar Support and Adjustable Arm Rests
Other Standard Features	Hour Meter, Electric Start, Cup Holder, Storage Tray, Front Step, Electric Fuel Gauge, Trailer Hitch Receiver