

Feature	Specifications
Engine	25.5 hp Kawasaki® FX801V
Horsepower	25.5
Cylinders	2
Oil Capacity	2.1 qt (2 L)
Drive System	Hydro-Gear® ZT-4400
Hydro Oil Cooler	N/A
Fuel Capacity	10.25 Gallon
Steering Control	Joystick, Twin Lever
Stand-up Deck	Standard
Pivoting Front Axle	Standard
Roll-Over Protection	Standard
Tires, Rear	24x9.5-12, 24x12-12
Tires, Front	13x6.5-6
Turning Radius	Zero-Turn
Ground Speed (Forward/Reverse)	11 mph/6 mph
Length	84"
Height : top of seat back	N/A
Height : top of ROPS extended	74"
Height : top of ROPS folded	47"
Width, Tractor (outside rear tires)	51", 56"
Width, Deck w/ Chute	65", 73"
Width, Deck Chute Up	53", 61"
Cutting Width	52", 60"
Cutting Height	1.5" - 5" (1/4" increments)
Deck Construction	Laminated Welded 10 Gauge Steel Deck with 10 Gauge Reinforcement and additional 7 Gauge Spindle Mounting Reinforcement, protective bullnose front, high impact anti-scalp rollers, and wear bar
Deck Engagement	Electric, Warner®
Blade Length	18.375", 21"
Spindle Assembly	Cast iron housing; 1.5" diameter shaft; maintenance free & field serviceable
Blade Tip Speed, approx.	19,000 fpm
Weight	1028 lbs - 1273 lbs
Seat	Suspension Seat with 2-1/4" Adjustable Travel, Vibration Isolators, Adjustable Seat Back Recline, Seat Back Pocket and Adjustable Arm Rests
Other Standard Features	Hour Meter, Electric Start, Cup Holder, Storage Tray, Front Step, Float Fuel Gauge, Trailer Hitch Receiver