



2021 XLT Specifications

Feature	Model				
	2448KAJ-C305	2452KAJ-C305	2452KAT-C305	2460KAJ-C305	2460KAT-C305
Product Name	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V
Engine	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V	Kawasaki FR730V
Horsepower	24	24	24	24	24
Cylinders	2	2	2	2	2
Oil Capacity	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)	2.2 qt (2.1 L)
Drive System	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100
Fuel Capacity	5 Gallon	5 Gallon	5 Gallon	5 Gallon	5 Gallon
Steering Control	Joystick	Joystick	Twin Lever	Joystick	Twin Lever
Stand-up Deck	Standard	Standard	Standard	Standard	Standard
ContourDTS™ Equipped	Standard	Standard	Standard	Standard	Standard
Tires, Rear	22x9.5-10	22x11-10	22x11-10	22x11-10	22x11-10
Tires, Front	13x6.5-6	13x6.5-6	13x6.5-6	13x6.5-6	13x6.5-6
Turning Radius	Zero-Turn	Zero-Turn	Zero-Turn	Zero-Turn	Zero-Turn
Ground Speed (Forward/Reverse)	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
Length	79"	79"	79"	79"	79"
Height : top of seat back	48"	48"	48"	48"	48"
Width, Tractor (outside rear tires)	47"	49"	49"	49"	49"
Width, Deck w/ Chute	61"	65"	65"	73"	73"
Width, Deck Chute Up	49"	53"	53"	61"	61"
Cutting Width	48"	52"	52"	60"	60"
Cutting Height	1.5" - 5" (1/4" Increments)				
Deck Construction	Laminated Welded 12 Gauge Steel Deck with 10 Gauge Reinforcement, including protective bullnose front & high impact anti-scalp rollers; 3/8" x 2" wear bar on trim edge				
Blade Engagement	Electric Clutch, Warner				
Blade Length	17"	18.375"	18.375"	21"	21"
Spindle Assembly	Cast Aluminum housing; 1" diameter shaft; maintenance free				
Blade Tip Speed, approx.	18,000 fpm	18,000 fpm	18,000 fpm	18,000 fpm	18,000 fpm
Weight	814 lbs	823 lbs	828 lbs	833 lbs	838 lbs
Seat	High Back, Enhanced Comfort Seat with adjustable slides				
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step, Hitch Plate				

Due to continuous product improvement, specifications are subject to change without notice.



2021 XLT Specifications

Feature	Model		
	2648KOJ-C305	2652KOJ-C305	2660KOJ-C305
Product Name	2648KOJ-C305	2652KOJ-C305	2660KOJ-C305
Engine	Kohler KT745	Kohler KT745	Kohler KT745
Horsepower	26	26	26
Cylinders	2	2	2
Oil Capacity	2 qt (1.9 L)	2 qt (1.9 L)	2 qt (1.9 L)
Drive System	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100	Hydro-Gear ZT-3100
Fuel Capacity	5 Gallon	5 Gallon	5 Gallon
Steering Control	Joystick	Joystick	Joystick
Stand-up Deck	Standard	Standard	Standard
ContourDTS™ Equipped	Standard	Standard	Standard
Tires, Rear	22x9.5-10	22x11-10	22x11-10
Tires, Front	13x6.5-6	13x6.5-6	13x6.5-6
Turning Radius	Zero-Turn	Zero-Turn	Zero-Turn
Ground Speed (Forward/Reverse)	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
Length	79"	79"	79"
Height : top of seat back	48"	48"	48"
Width, Tractor (outside rear tires)	47"	49"	49"
Width, Deck w/ Chute	61"	65"	73"
Width, Deck Chute Up	49"	53"	61"
Cutting Width	48"	52"	60"
Cutting Height	1.5" - 5" (1/4" Increments)		
Deck Construction	Laminated Welded 12 Gauge Steel Deck with 10 Gauge Reinforcement, including protective bullnose front & high impact anti-scalp rollers; 3/8" x 2" wear bar on trim edge		
Blade Engagement	Electric Clutch, Warner		
Blade Length	17"	18.375"	21"
Spindle Assembly	Cast Aluminum housing; 1" diameter shaft; maintenance free		
Blade Tip Speed, approx.	18,000 fpm	18,000 fpm	18,000 fpm
Weight	805 lbs	814 lbs	824 lbs
Seat	High Back, Enhanced Comfort Seat with adjustable slides		
Other Standard Features	Hour Meter, Electric Start, Arm Rest, Cup Holder, Front Step, Hitch Plate		

Due to continuous product improvement, specifications are subject to change without notice.