



## TRAILBLAZER(TM) Mid-Duty Specifications

<b>Imperial</b>	<b>5' 6"</b>	<b>6' 0"</b>
Blade Width	5' 6"	6' 0"
Blade Height	19.67"	19.67"
Blade Gauge	16	16
Trip Springs	2	2
Vertical Ribs	4	4
Lift Cylinder (Single Acting)	1 ½" x 3" (one)	1 ½" x 3" (one)
Angling Rams (Double Acting)	1 ½" x 4"	1 ½" x 4"
Plowing Width	4' 11"	5' 4"
Approx. Weight*	190 lb	195 lb
Cutting Edge	¼" x 4"	¼" x 4"
Mount Type	Mid-Duty UTV Mounting System	Mid-Duty UTV Mounting System

<b>Metric</b>	<b>5' 6"</b>	<b>6' 0"</b>
Blade Width	1.68 m	1.83 m
Blade Height	50 cm	50 cm
Blade Gauge	0.15 cm	0.15 cm
Trip Springs	2	2
Vertical Ribs	4	4
Lift Cylinder (Single Acting)	3.8 cm x 7.6 cm	3.8 cm x 7.6 cm
Angling Rams (Double Acting)	3.8 cm x 10.2 cm	3.8 cm x 10.2 cm
Plowing Width	1.50 m	1.63 m
Approx. Weight*	86.2 kg	88.5 kg
Cutting Edge	0.6 cm x 10.2 cm	0.6 cm x 10.2 cm
Mount Type	Mid-Duty UTV Mounting System	Mid-Duty UTV Mounting System

\*Does not include vehicle mount. Please refer to the eMatch program for specific vehicle applications.