

SPEED»CASTER™

TAILGATE SPREADERS



SPEED»CASTER™ 525

SPEED»CASTER™ 900

The Right Material in the Right Place. FISHER® SPEED-CASTER™ 525 and SPEED-CASTER™ 900 tailgate spreaders are designed to give you the ultimate ice control versatility. Each features a 2-stage, auger-fed delivery system that spreads bagged or bulk sand, salt or a sand/salt mix with precise control. With a mounting system that accommodates pickups, SUVs and tractors, FISHER tailgate spreaders deliver exceptional performance in virtually any application.

The Legacy Rolls On



SPEED»CASTER™

FOR THE ULTIMATE IN VERSATILITY,
EVERYONE NEEDS A GOOD UTILITY PLAYER

SPEED»CASTER™ 525

5.25 CU FT TAILGATE SPREADER

- Holds up to 420 lb of bagged or bulk de-icing material
- Comes standard with a combination 2" Receiver Hitch and 3-point Combo Mount

SPEED»CASTER™ 900

9.00 CU FT TAILGATE SPREADER

- Holds up to 720 lb of bagged or bulk de-icing material
 - Available options include Pivot Mount, 2" Receiver Hitch (requires Adapter Mount) and 3-point Hitch Mount.
- *Mounts sold separately.



VARIABLE SPEED CONTROL

Enhanced dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions. Three standard accessory buttons and a dedicated blast button provide optimum in-cab efficiency. Easy-to-understand, digital self-diagnostics alert the operator when the spreader is empty or when adjustments are needed, and LEDs make the control easy to read. Its compact size compared to traditional controls fits easily into today's modern truck cab designs.

DUAL ELECTRIC MOTORS

Two instant-start, 12-volt electric motors provide quiet, reliable, independent control over the auger and spinner mechanisms. The spinner motor is sealed inside a weather-resistant housing, protecting it from corrosion.

OTHER FEATURES

- Heavy-duty horizontal auger built of solid powder coated steel for strength and performance
- 10" nylon/glass reinforced resin (SPEED-CASTER™ 525) and 12" steel (SPEED-CASTER™ 900) spinners for a long, low-maintenance life
- Steel-rod top screen to break up chunks while loading for improved performance
- Molded polyethylene lid to protect material from the elements
- Standard vibrating inverted V to break up clumps and ensure smooth material flow

SPECIFICATIONS

Model	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	Approximate Weight (empty)	Electric Motor	Auger (Diam. x Length)	Spinner Size	Spreading Width	Materials	Vehicle Application	Available Mounts
SPEED-CASTER 525	5.25 cu ft (0.15 cu m)	Polyethylene	20½" x 38" x 34" (52.10 cm x 96.50 cm x 86.40 cm)	160 lb (72.6 kg)	Dual, 12-volt 1/3 hp	3" x 14" Heavy-Duty Solid Steel (7.62 cm x 35.56 cm)	10" (25.40 cm)	Up to 30' (Up to 9.14 m)	Bagged Rock Salt, Sand, 50/50 Salt/Sand Mix	Tractors, SUVs, 1-Ton or Smaller Pickups	Standard 2" Receiver, 3-point Combo Mount
SPEED-CASTER 900	9.00 cu ft (0.25 cu m)	Polyethylene	24" x 52" x 36" (60.90 cm x 132.10 cm x 91.40 cm)	180 lb (81.7 kg)	Dual, 12-volt 1/3 hp	3" x 20" Heavy-Duty Solid Steel (7.62 cm x 50.80 cm)	12" (30.50 cm)	Up to 40' (Up to 12.19 m)	Bagged Rock Salt, Sand, 50/50 Salt/Sand Mix	Tractors, 1-Ton or Smaller Pickups	Pivot Mount, 2" Receiver Hitch (requires Adapter Mount), 3-point Hitch Mount



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle ratings with a spreader. This product is manufactured under the following US patent 6,253,470; 6,422,490; 7,400,058; 7,737,576; CAN patent 2,300,474. Fisher Engineering offers a limited warranty on all spreaders and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, SPEED-CASTER™ 525, SPEED-CASTER™ 900.