



STEEL-CASTER™ Specifications

Specifications

| Imperial | 7' 1.5 cu yd | 8' 2.0 cu yd | 9' 3.0 cu yd | 9' 4.5 cu yd | 10' 4.5 cu yd | 10' 6.0 cu yd |
|----------------------------|----------------------------|----------------------------|---|---|---|---|
| Body Side Length | 7' | 8' | 9' | 9' | 10' | 10' |
| Capacity | 1.5 cu yd | 2.0 cu yd | 3.0 cu yd | 4.5 cu yd | 4.5 cu yd | 6.0 cu yd |
| Hopper Construction | 16 ga SS | 16 ga SS | 16 ga SS | 16 ga SS | 16 ga SS | 16 ga SS |
| Dimensions Overall (LxWxH) | 84" x 50" x 38" | 96" x 50" x 33" | 108" x 50" x 41" | 108" x 70" x 47" | 120" x 70" x 47" | 120" x 70" x 54" |
| Dual 12V DC Sealed Motors | 595 lb | 615 lb | 695 lb | 815 lb | -- | -- |
| Gas 10.5 hp I/C Briggs | -- | 740 lb | 820 lb | 940 lb | 965 lb | 1010 lb |
| Gas 11 hp I/C Honda | -- | 740 lb | 820 lb | 940 lb | 965 lb | 1010 lb |
| Dual Hydraulic Motors | -- | 615 lb | 695 lb | 815 lb | 840 lb | 885 lb |
| Conveyor Width | 16 ½" | 16 ½" | 16 ½" | 16 ½" | 16 ½" | 16 ½" |
| Spinner Size | 15 ½" | 15 ½" | 15 ½" | 15 ½" | 15 ½" | 15 ½" |
| Spreading Width | Up to 40' | Up to 40' | Up to 40' | Up to 40' | Up to 40' | Up to 40' |
| Materials | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix |
| Vehicle Application | 3/4- & 1-Ton Pickup Trucks | 3/4- & 1-Ton Pickup Trucks | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) |

| Metric | 7' 1.5 cu yd | 8' 2.0 cu yd | 9' 3.0 cu yd | 9' 4.5 cu yd | 10' 4.5 cu yd | 10' 6.0 cu yd |
|----------------------------|-------------------------|-------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| Body Side Length | 2.13 m | 2.44 m | 2.74 m | 2.74 m | 3.05 m | 3.05 m |
| Capacity | 1.15 cu m | 1.53 cu m | 2.29 cu m | 3.44 cu m | 3.44 cu m | 4.59 cu m |
| Hopper Construction | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS |
| Dimensions Overall (LxWxH) | 214 cm x 127 cm x 97 cm | 244 cm x 127 cm x 84 cm | 275 cm x 127 cm x 105 cm | 275 cm x 178 cm x 120 cm | 305 cm x 178 cm x 120 cm | 305 cm x 178 cm x 138 cm |
| Dual 12V DC Sealed Motors | 269.89 kg | 278.96 kg | 315.25 kg | 369.68 kg | -- | -- |
| Gas 10.5 hp I/C Briggs | -- | 335.66 kg | 371.95 kg | 426.38 kg | 437.72 kg | 458.13 kg |
| Gas 11 hp I/C Honda | -- | 335.66 kg | 371.95 kg | 426.38 kg | 437.72 kg | 458.13 kg |
| Dual Hydraulic Motors | -- | 278.96 kg | 315.25 kg | 369.68 kg | 381.02 kg | 401.43 kg |
| Conveyor Width | 42 cm | 42 cm | 42 cm | 42 cm | 42 cm | 42 cm |
| Spinner Size | 40 cm | 40 cm | 40 cm | 40 cm | 40 cm | 40 cm |



STEEL-CASTER™ Specifications

| | | | | | | |
|---------------------|-------------------------------|-------------------------------|--|--|--|--|
| Spreading Width | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m |
| Materials | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix | Salt, Sand, Salt/Sand Mix |
| Vehicle Application | 3/4- & 1-Ton Pickup Trucks | 3/4- & 1-Ton Pickup Trucks | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (over 15,000 lb GVWR) |