

48"

MODEL - 992520

22 HP / Kawasaki® FX691V Engine

52"

MODEL - 992521

22 HP / Kawasaki® FX691V Engine

60"

MODEL - 992522

23.5 HP / Kawasaki® FX730V Engine

MODEL - 992524

25 HP / Kohler® ZT740 Engine

MODEL - 992523

26 HP / 999 Kawasaki® FT730 EFI Engine

MODEL - 992526

31 HP /Kawasaki® FX921V

72"

MODEL - 992525

31 HP / 999 Kawasaki® FX921V Engine

COMFORTABLE SEAT High back seat has lumbar support and molded armrests. Its red double stitching gives a high-end look with black, dark grey, and red accents.

FULLY WELDED TUBULAR FRAME One glace and you can see its strength and ruggedness. Its wide front rail distributes weight for superior balance.

Also supports the deck lift for easy engagement. Includes a limited lifetime warranty.

PARKER TRANSAXLES Parker HTJ transaxles deliver a top speed of 11mph and have a 12cc pump. Filters are easily accessed from the rear for easy maintenance. This is one complete system which eliminates the need for additional parts, saving both time and money.

X-FACTOR® 3 Made with 7-gauge steel and specially designed for better grass dispersion thanks to its larger discharge opening, integrated baffles, and sloped front end. Reinforced spindle mounts protect blade operation while the six recessed anti-scalp wheels protect the turf on uneven terrain. Its flip-up rubber chute makes it easy to drive through gates and around obstacles. A 5/8" leading edge provides extra protection to the shell while stabilizer links keep vibration to a minimum. Includes a limited lifetime warranty.

DIAL HEIGHT ADJUSTMENT The dial wheel allows easy height adjustment between one and five inches. Toolless adjustable foot pedal with internal assist springs helps lift the deck with little effort.

PRO-TURN 300



See your professional Gravely® dealer for complete warranty details.

	348	352	360	360	360	360	372
MODEL NUMBER	992520	992521	992522	992524	992523	992526	992525
ENGINE	KAWASAKI FX691V	KAWASAKI FX691V	KAWASAKI FX730V	KOHLER ZT740	KAWASAKI FT730 EFI	KAWASAKI FX921V	KAWASAKI FX921
HORSEPOWER	22 HP	22 HP	23.5 HP	25 HP	26 HP	31 HP	31 HP
DISPLACEMENT	726 CC	726 CC	726 CC	747 CC	726 CC	999 CC	999 CC
DRIVE SYSTEM	PARKER HTJ TRANSMISSION						
FUEL CAPACITY	12.5 GAL						
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	11 MPH / 5 MPH						
DECK							
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT						
DECK CONSTRUCTION	X-FACTOR® 3 DECK						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	18,000						
SPINDLE HOUSING MATERIAL				FORGED ALUMINUM			
SPINDLE BEARINGS				BALL BEARING			
DECK ENGAGEMENT	OGURA GT2.75					OGURA GT3.5	
CUTTING WIDTH	48 IN.	52 IN.	60 IN.	60 IN.	60 IN.	60 IN.	72 IN.
CUTTING HEIGHTS	1.0 IN 5.5 IN.						
CUTTING POSITIONS				19			
WHEELS							
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES						
FRONT	SMOOTH 15 X 6-6 PNEUMATIC						
REAR	24 X 12-16 BIAS PLY TURF						
FEATURES							
SEAT	SUSPENSION PLUSH SEAT WITH ARM RESTS						
FOLDABLE ROPS	STANDARD						
MACHINE							
WEIGHT	1235 LBS.	1320 LBS.	1347 LBS.	1333 LBS.	1347 LBS.	1350 LBS.	1472 LBS.
LENGTH	84 IN.	84 IN.	84 IN.	84 IN.	84 IN.	84 IN.	86.2 IN.
WIDTH (w/o CHUTE)	51 IN.	55 IN.	63 IN.	63 IN.	63 IN.	63 IN.	75 IN.
WIDTH (w/ CHUTE)	63 IN.	67 IN.	75 IN.	75 IN.	75 IN.	75 IN.	87 IN.
HEIGHT (w/ ROPS EXT/ DOWN)	76.0 IN. /47.8 IN.						
WARRANTY							
UNIT	5 YEAR/1250 HOUR COMMERCIAL/NO HOUR LIMIT FIRST 2 YEARS- SEE YOUR PROFESSIONAL GRAVELY DEALER FOR COMPLETE WARRANTY DETAILS						
DECK SHELL & FRAME				LIMITED LIFETIME			

MULCHING KIT, ELECTRIC DECK LIFT KIT, TRAILER KIT KIT, LED HEADLIGHT KIT, POWERED BAGGER KIT, OCDC KIT, SUNSHADE KIT, REAR TWEEL KIT, RADIAL DRIVE CONVERSION KIT, WHEEL COVER KIT, LASEREDGE BLADE KIT, TUNE UP KIT

