

SUCCESS IS CONTAGIOUS.

Consistent cutting results, comfort for the long haul, and a choice of three sized mower decks make the Pro-Turn® 100 a great value. It can handle the toughest jobs you can dish out and will be ready for more the next day.



48 MODEL - 991128 22 HP / 726 CC Kawasaki[®] FX691V Engine

GRAVELY

52 MODEL - 991129 22 HP / 726 CC Kawasaki[®] FX691V Engine

MODEL - 991132 23 HP / 747 CC Kohler[®] ZT730 Engine **60 MODEL - 991130** 23.5 HP / 726 CC Kawasaki[®] FX730V Engine

MODEL - 991133 25 HP / 747 CC Kohler[®] EZT740 Engine

CBT SYSTEM Our exclusive Constant Belt Tension System (CBT) ensures that belt tension is constant, keeping the blade tip speed and cutting results consistent.

X-FACTOR® II DECK Fabricated from top to bottom, it provides industrial-strength peace of mind.

SEATING SYSTEM The high-back suspension seat provides improved lateral stability with added vibration control and a 4-inch seat slide for all-day comfort.

PRO-TURN[®] 100



See your professional Gravely® dealer for complete warranty details.

	148	152	152	160	160
MODEL NUMBER	991128	991129	991132	991130	991133
ENGINE	KAWASAKI° FX691V	KAWASAKI° FX691V	KOHLER° ZT730	KAWASAKI° FX730V	KOHLER [®] ZT740
		AIR-C	COOLED, HEAVY-DUTY AIR CLEAN	NER	
HORSEPOWER	22 HP	22 HP	23 HP	23.5 HP	25 HP
DISPLACEMENT (cc)	726 CC	726 CC	747 CC	726 CC	747 CC
DRIVE SYSTEM	HYDRO-GEAR [®] ZT-3400 TRANSAXLES				
FUEL CAPACITY – Gallons (Liters)	10 GAL				
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	10 MPH / 5 MPH				
DECK					
DECK MATERIAL	7 GA. STEEL W/ 1/4 IN. SPINDLE REINFORCEMENT				
DECK CONSTRUCTION	FABRICATED				
NUMBER OF SPINDLES	3				
BLADE TIP SPEED (FPM)	18,000				
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM				
SPINDLE BEARINGS	BALL BEARING				
DECK ENGAGEMENT	OGURA" GT 2.75 ELECTRIC CLUTCH				
CUTTING WIDTH	48 IN	52 IN	52 IN	60 IN	60 IN
CUTTING HEIGHTS	1.0 IN - 5.0 IN				
CUTTING POSITIONS			17		
WHEELS					
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES				
RONT	SM00TH 13 X 6.50 - 6				
REAR	TURF 23 X 10.50 - 12				
FEATURES					
SEAT	HIGH BACK W/ FULL SUSPENSION AND MOLDED ARM RESTS				
FOLDABLE ROPS			STANDARD		
MACHINE					
WEIGHT	1062 LBS	1079 LBS	1068 LBS	1121 LBS	1110 LBS
LENGTH			78.5 IN		
WIDTH (w/o CHUTE)	50 IN	55.5 IN	55.5 IN.	63 IN	63 IN
WIDTH (w/ CHUTE)	62 IN	67.5 IN	67.5 IN	75 IN	75 IN
HEIGHT (w/ ROPS EXT/DOWN)			68 IN. / 48 IN		
WARRANTY					
UNIT	5 YEAR / 1000 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YOUR PROFESSIONAL GRAVELY® DEALER FOR COMPLETE WARRANTY DETAILS				

MULCHING KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, BAGGER KIT, SEMI-PNEUMATIC FRONT TIRE KIT, WHEEL COVER KIT, RADIAL DRIVE CONVERSION KIT, OCDB KIT, LASEREDGE BLADES, TUNE UP KIT



SCAN TO VIEW

© Copyright 2021 AriensCo. All rights reserved. Registered trademark and ³⁴ trademark of Ariens Company. Briggs & Stratton*, Kohler*, Kawasaki*, Subaru*, Ya-maha* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufactur-er to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

