

GET MUCH MORE THAN YOU PAY FOR.

Don't let its price-point fool you. The Pro-Turn® ZX still delivers a great Gravely performance, making it a great value. Its solid construction can handle the toughest commercial jobs and leave a beautifully manicured lawn behind it. This is definitely a "big return on a small investment" situation.



48 MODEL - 991286 22 HP / 726 CC Kawasaki[®] FX691V Engine

RAVEL

52 MODEL - 991288 22 HP / 726 CC Kawasaki[®] FX691V Engine

60 MODEL - 991290 23.5 HP / 726 CC Kawasaki[®] FX730V Engine

AN AUTOMOTIVE-STYLE TUBULAR FRAME It's unique to the mowing industry and increases durability by withstanding force from any direction. This high-strength, premium frame is positioned with a lower center of gravity to improve stability while mowing on hillsides.

ZT-3200° TRANSAXLES They're more heavy duty and can handle higher speeds. They're also commercial grade and serviceable for a longer life span.

X-FACTOR[®] 3 DECK The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

PRO-TURN ZX



See your professional Gravely® dealer for complete warranty details.

	48	52	60
10DEL NUMBER	991286	991288	991290
INGINE	KAWASAKI° FX691V	KAWASAKI° FX691V	KAWASAKI° FX730V
IORSEPOWER	22 HP	22 HP	23.5 HP
DISPLACEMENT	726 CC		
ORIVE SYSTEM	HYDRO-GEAR" ZT-3200 TRANSAXLES		
UEL CAPACITY	5.0 GAL		
ROUND SPEED APPROX. Mph) - (Forward/Reverse)		8.5 MPH / 4 MPH	
DECK			
DECK MATERIAL	10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT		
DECK CONSTRUCTION	FABRICATED X-FACTOR" 3		
IUMBER OF SPINDLES	3		
BLADE TIP SPEED (FPM)	18,000		
PINDLE HOUSING MATERIAL	FORGED ALUMINUM		
PINDLE BEARINGS	BALL BEARING		
ECK ENGAGEMENT		OGURA [®] GT1.5 ELECTRIC CLUTCH	
UTTING WIDTH	48 IN	52 IN	60 IN
UTTING HEIGHTS		1.5 IN - 5.0 IN	
UTTING POSITIONS		15	
VHEELS			
RONT AXLE	SUSPENSION, GREASABLE CASTER FORK TUBES		
RONT		SM00TH 13 X 6.50-6	
REAR	TURF 22 X 10-12	TURF 22 X 10.5-12	TURF 22 X 12-12
EATURES			
EAT	HIGH BACK COMFORT W/ SUSPENSION & PADDED ARMRESTS		
OLDABLE ROPS	STANDARD		
ACHINE			
VEIGHT	925 LBS	931 LBS	952 LBS
ENGTH		79 IN	
VIDTH (w/o CHUTE)	50.8 IN	56.2 IN	63.7 IN
VIDTH (w/ CHUTE)	61.9 IN	67.3 IN	74.8 IN
IEIGHT w/ ROPS EXT/DOWN)	72 IN / 52 IN		
VARRANTY			
		EE YOUR PROFESSIONAL GRAVELY® DEALER FOR CO	

ATTACHMENTS & ACCESSORIES

MULCHING KIT, OCDB KIT, TRAILER HITCH KIT, LED HEADLIGHT KIT, AGGRESSIVE REAR TIRE KIT, STRIPING KIT, SUNSHADE KIT, POWERED BAGGER KIT, REAR TWEEL KIT, SUSPENSION SEAT KIT, SEMI-PNEUMATIC FRONT TIRE KIT, WHEEL COVER KIT, LASEREDGE BLADES, TUNE UP KIT



SCAN TO VIEW

PRODUCT ONLINE

© Copyright 2021 AriensCo. All rights reserved. Registered trademark and [™] trademark of Ariens Company. Briggs & Stratton*, Kohler*, Kawasaki*, Subaru*, Yamaha* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacture rot to be used for comparison purpose only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacture power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

