

SPREADER SPECIFICATIONS

Standard ☒ Metric

MODEL	800TR	1200 TR	1500 TR	1900 TR
Overall width	59"	80"	80"	80"
Height	59"	66"	71"	75"
Depth	58"	49"	49"	49"
Capacity (water level)	0.7 cu yd	1.0 cu yd	1.4 cu yd	1.7 cu yd
Capacity (rounded)	0.8 cu yd	1.2 cu yd	1.5 cu yd	1.9 cu yd
Weight (empty)	705 lb	1610 lbs	1665 lbs	1720 lbs
Hopper construction	Poly	Poly	Poly	Poly
Spreading width	3-30 ft (may vary depending on material)	2'-40' (may vary depending on material)		
Spinner size	15"	20"	20"	20"
Auger diameter	2.5"	4.5"	4.5"	4.5"
Vehicle	Tractors / loaders			
Material	Salt, sand, granulat/mixed (max 5/16" ø)			

LIQUID SYSTEM (optional)

Standard ☒ Metric

MODEL	800 TR	1200 TR	1500 TR	1900 TR
Pre-wet, Spray volume	0.8-3.2 gal/min	0.8-3.2 gal/min	0.8-3.2 gal/min	0.8-3.2 gal/min
Spraybar, Spray volume	20 gal/lane mile at 10-20 mph			
Pre-wet, Spraying width	3-26 ft (together with spreading material)			
Spraybar, Spraying width	7-16 ft	7-16 ft	7-16 ft	7-16 ft
Pre-wet, liquid tank capacity	87 gal	120 gal	120 gal	120 gal
Spraybar, liquid tank capacity	87-238 gal*	120-320 gal*	120-320 gal*	120-320 gal*
Spraying material	Anti- and de-icing liquids, water, liquid fertilizers **			

* With optional patented bladder tank inside for spray bar system

** Do not use flammable or petroleum liquids for the liquid system