

ALL-NEW MODELS
POWER PUSHER™ & POWER PUSHER PRO

FIXED WING & HYDRAULIC WING PUSHER PLOWS – 30" HIGH | 12', 14', & 16' WIDE

SnowEx✓





Push forward like never before with the POWER PUSHER™ family of fixed wing and hydraulic wing pusher plows that move massive amounts of snow with every pass. The 30" high pusher box in the 12', 14', and 16' widths are optimized for fast snow clean-up by compact loaders and tractors.

TRACE™ EDGE TECHNOLOGY (all models)

The terrain-response advanced cutting edge is comprised of independent 2' sections that raise, oscillate, and trip to accommodate contours and obstacles in the plowable surface. Working together, the sections remove more snow, reducing the amount of salt required.

3/4" CUTTING EDGE WITH CARBIDE INSERTS (all models)

Each 2" cutting edge section comes standard with a 3/4" cutting edge with carbide insert that extends the life of a high-carbon blade up to 20 times. And each section uses the same part number for easy replacement. No need to replace the full cutting edge, only the section(s) that show wear.

EASY OPERATION (all models)

Operation of the POWER PUSHER family of pushers is tied conveniently into the vehicle's controls. Simply raise and lower the lift arm and angle the attachment plate to position the pusher in the correct orientation. The POWER PUSHER PRO pusher wings are tied into the auxiliary hydraulic functions of the vehicle.

180° INFINITELY VARIABLE WING PLACEMENT (POWER PUSHER PRO)

Hydraulically actuated, 3' wings can be moved into countless configurations within the 180-degree path of travel. Both wings move independently and 6' of plow width is added when both wings are fully open.

	POWER PUSHER™ Fixed Wing Pushers			POWER PUSHER PRO Hydraulic Wing Pushers		
Moldboard Options	Powder-Coated Steel			Powder-Coated Steel		
Blade Width	12' (3.66 m)	14' (4.27 m)	16' (4.88 m)	12' (3.66 m)	14' (4.27 m)	16' (4.88 m)
Blade Height	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)
Side Plate Width	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)	36" (91.44 cm)
Side Plate Height	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)	30" (76.20 cm)
Approximate Weight (w/o mount)	2,544 lb (1,156.4 kg)	2,911 lb (1,323.2 kg)	3,145 lb (1,429.5 kg)	2,950 lb (1,340.9 kg)	3,317 lb (1,507.7 kg)	3,551 lb (1,614.1 kg)
Moldboard Radius	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)	27" (68.58 cm)
Approximate Snow Capacity	113 cu ft (3.20 cu m)	132 cu ft (3.73 cu m)	151 cu ft (4.28 cu m)	113 cu ft (3.20 cu m)	132 cu ft (3.73 cu m)	151 cu ft (4.28 cu m)
Wing Movement	Fixed Wing			Infinitely variable on a 180°-arc of travel		
Cutting Edge Technology	TRACE™ - Terrain Response Advanced Cutting Edge			TRACE™ - Terrain Response Advanced Cutting Edge		
Cutting Edge Material	High Carbon Steel with Carbide Inserts			High Carbon Steel with Carbide Inserts		
Mount Type	Skid Steer Attach Plate/Coupler			Skid Steer Attach Plate/Coupler		
Horsepower Compatibility	40+ hp Tractor 60+ hp Wheel Loader			40+ hp Tractor 60+ hp Wheel Loader		
Vehicle Compatibility	Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors			Compact Wheel Loaders, Wheel Loaders (9,000-25,000 lb), Skid Steers (9,000 lb+), Tractors		

TrynEx International | Madison Heights, Michigan 48071

snowexproducts.com

2 WINTER WARRANTY

TrynEx International reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. TrynEx International or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings. Other patents pending. TrynEx International offers a limited warranty for all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: TRACE™, POWER PUSHER®, SnowEx®