

# SPECIFICATIONS

## Select Your Engine

**Kawasaki FX1000E**



Close All

## ENGINE



### **ENGINE NAME**

Kawasaki FX1000E

### **HORSEPOWER**

38.5HP

### **FUEL CAPACITY**

9.5gal

## DRIVE LINE



### **HYDRAULIC DRIVE**

Parker HTG Transaxles - 16cc Drive Motors

### **HYDRAULIC DRIVE TORQUE**

Continuous - 498 ft-lb | Max Torque - 587 ft-lb

### **HYDRO DRIVE MAINTENANCE**

1000 Hours Between Oil Changes

### **DRIVE TIRES**

61" , 72" - 24x12-R12 Radial

### **FRONT TIRES**

13x6.5-R6 Radial with Optional No Flats, or Tweels



### **WHEELS TYPE**

Aluminum rear wheels and front hub covers

---

### **SPEED (F/R)**

Forward - Up to 13mph | Reverse - Up to 5mph

---

## **FEATURES**

---



### **SEAT**

Smart Ride Technology w/ full suspension seat - adjustable TecPak Elastomer supports - 360 degree floating seat platform - independent rear frame section suspended by Winamac coil springs

---

### **STEERING LEVERS**

Soft-Touch Knobs to Adjust Forward and Back. Adjustable Up and Down

---

### **CONTROL PANEL LCD DISPLAY**

N/A

---

### **CONTROL PANEL LED WARNING INDICATORS**

N/A

---

### **IGNITION**

Key Switch

---

### **AUXILIARY POWER**

12v Outlet Next to Phone Holder

---

### **STORAGE**

Phone Holder, Cup Holder, and Deep Storage Tray

---

### **HITCH**

2" Rear Receiver Standard

---

## **CUTTING DECK**

---



### **DECK SIZES**

61", 72"

---

### **DECK DEPTH**

6" Deep, Reinforced 7 Gauge Full-Floating Deck

---

### **DECK LIFT**

Foot Operated with Shock Assist

---

### **DECK ADJUSTMENT**

Magnetic Pin Height Adjustment

---

### **CUT HEIGHT**

1" to 5" with 15 Cut Heights



---

**BLADE SPINDLES**

Cast Aluminum, No Maintenance/Sealed Bearings

---

**PARKING BRAKE**

Foot Operated

---

**FRAME**

1.5" by 3" Powder Coated Fusion-Bonded Solid Steel Bridge Frame

---

**MEASUREMENTS** **WIDTH**

61" Deck - 62.5" Wide | 72" Deck - 73.5" Wide

---

**WEIGHT**

61" Deck - 1290lbs | 72" Deck - 1323lbs

---

**LENGTH**

84"

---

**HEIGHT**

75" with ROPS Up - 54" with Folding ROPS Down

---

**WARRANTY** **ENGINE WARRANTY**

3 Year

---

**FULL WARRANTY**

3 Year / 500 Hours Residential - 2 Year / Unlimited Hour Commercial - 120 Day Belt Warranty

---

**DECK WARRANTY**

Lifetime on the leading edge

---

**HYDRAULIC DRIVE WARRANTY**

3 Year / 1500 Hour

---

**CONTROL PANEL WARRANTY**

3 Year

---



## Select Your Engine

Vanguard Big Block EFI/ETC



Close All

### ENGINE



#### **ENGINE NAME**

Vanguard Big Block EFI/ETC

#### **HORSEPOWER**

40HP

#### **FUEL CAPACITY**

9.5gal

### DRIVE LINE



#### **HYDRAULIC DRIVE**

Parker HTG Transaxles - 16cc Drive Motors

#### **HYDRAULIC DRIVE TORQUE**

Continuous - 498 ft-lb | Max Torque - 587 ft-lb

#### **HYDRO DRIVE MAINTENANCE**

1000 Hours Between Oil Changes

#### **DRIVE TIRES**

61" , 72" - 24x14-R12 Radial

#### **FRONT TIRES**

13x6.5-R6 Radial with Optional No Flats, or Tweels



### **WHEELS TYPE**

Aluminum rear wheels and front hub covers

---

### **SPEED (F/R)**

Forward - Up to 13mph | Reverse - Up to 5mph

---

## **FEATURES**

---



### **SEAT**

Smart Ride Technology w/ full suspension seat - adjustable TecPak Elastomer supports - 360 degree floating seat platform - independent rear frame section suspended by Winamac coil springs

---

### **STEERING LEVERS**

Soft-Touch Knobs to Adjust Forward and Back. Adjustable Up and Down

---

### **CONTROL PANEL LCD DISPLAY**

N/A

---

### **CONTROL PANEL LED WARNING INDICATORS**

N/A

---

### **IGNITION**

Key Switch

---

### **AUXILIARY POWER**

12v Outlet Next to Phone Holder

---

### **STORAGE**

Phone Holder, Cup Holder, and Deep Storage Tray

---

### **HITCH**

2" Rear Receiver Standard

---

## **CUTTING DECK**

---



### **DECK SIZES**

61", 72"

---

### **DECK DEPTH**

6" Deep, Reinforced 7 Gauge Full-Floating Deck

---

### **DECK LIFT**

Foot Operated with Shock Assist

---

### **DECK ADJUSTMENT**

Magnetic Pin Height Adjustment

---

### **CUT HEIGHT**

1" to 5" with 15 Cut Heights



---

**BLADE SPINDLES**

Cast Aluminum, No Maintenance/Sealed Bearings

---

**PARKING BRAKE**

Foot Operated

---

**FRAME**

1.5" by 3" Powder Coated Fusion-Bonded Solid Steel Bridge Frame

---

**MEASUREMENTS** **WIDTH**

61" cut - 62.5" wide | 72" cut - 73.5" wide

---

**WEIGHT**

61" - 1303lbs | 72" - 1336lbs

---

**LENGTH**

84"

---

**HEIGHT**

75" with ROPS Up - 54" with Folding ROPS Down

---

**WARRANTY** **ENGINE WARRANTY**

3 Year

---

**FULL WARRANTY**

3 Year / 500 Hour Residential - 2 Year / Unlimited Hour Commercial - 120 Day Belt Warranty

---

**DECK WARRANTY**

Lifetime on the leading edge

---

**HYDRAULIC DRIVE WARRANTY**

3 Year / 1500 Hour

---

**CONTROL PANEL WARRANTY**

3 Year

---

