

GT SERIES SLIDE-AWAY GATE



3,300 lb, 4,000 lb and 5,500 lb Capacities

**DESIGNED TO SIMPLIFY
INSTALLATION AND TO MAXIMIZE
TRAILER EFFICIENCY.**



Products shown may feature optional equipment. Content subject to change without notice.

STANDARD GT SERIES ADVANTAGES INCLUDE:

- Can be mounted on trailers with either swing-type or roll up doors.
- Does not add to trailer length, making it ideal for 53-foot trailer applications.
- Mounts easily to most dry-freight and refrigerated trailers.
- Requires no modification of trailer sills up to 21 1/4" deep, and no moving of OEM lights or door hardware.
- Requires only 64 1/2" to 77 1/2" behind the rear axle for mounting.
- Large, single-fold, level ride platform featuring a rugged steel main section and a lightweight aluminum folding section.
- Stores completely underneath the trailer eliminating the potential for backing damage at loading docks.
- It allows you to completely seal at cushioned docks.
- Since it is shipped completely assembled and tested from the factory, installation is significantly simplified.
- Bolt on design allows easy removal and/or transfer.
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion.



The liftgate can be certified to meet Canadian Rear Impact Guard Standard 22 (Available option)

Large level ride platform makes it ideal for a wide variety of trailer distribution applications.

Stored completely underneath the trailer, the GT Slide-Away Gate does not add to trailer length and requires no modification of trailer sills, OEM lights or door hardware.



Mounting the GT requires only 64 1/2" behind the rear axle



1 Stores Completely Underneath Trailer



2 Powers Out from Under Trailer



3 Manually Unfold Aluminum Extension



4 Liftgate Positioned for Cargo Loading




Designed Simplicity - Maximum Performance

www.waltco.com

GT SERIES SLIDE-AWAY GATE



Stores completely underneath the trailer



Thermally protected power unit



Optional Cart Stop



Optional Side Access Ramp

SPECIFICATIONS

Bed Ht: 45"-64"

Model	Capacity	Platform	Ramp	Weight
GT - 33	3,300 lbs.	70" x 80"	12" Folding	2,024 lbs.
GT - 33	3,300 lbs.	80" x 80"	12" Folding	2,168 lbs.
GT - 44	4,400 lbs.	70" x 80"	12" Folding	2,024 lbs.
GT - 44	4,400 lbs.	80" x 80"	12" Folding	2,168 lbs.
GT - 55	5,500 lbs.	70" x 80"	12" Folding	2,051 lbs.
GT - 55	5,500 lbs.	80" x 80"	12" Folding	2,195 lbs.

Typical Ground Clearance Dimensions:

48" bed height has 17 1/4" ground clearance' 55" bed height has 24 1/4" ground clearance

OTHER STANDARD FEATURES:

- Thermally protected power unit safeguards liftgate motor from damage due to heat build-up.
- Reduced Maintenance™ features including: self-lubricating, fiberglass-reinforced Teflon® bearings at key pivot points and closed-loop hydraulic system.
- Factory-installed fully-sealed raise/lower, open/close switches.
- Super Duty Motor for increased motor run time and less wear and tear in high cycle applications.
- Weather protective enclosure to shield power unit and vital components from environmental damage.
- Electrical Wiring meets or exceeds all TMC Recommended Practices, including 150-amp circuit breaker protection.
- (2) 12-Volt Group 31 Batteries.
- DOT Certified, depending on bed height and "A" dimension.

OPTIONAL EQUIPMENT:

- Canadian Rear Impact Guard Configuration.
- Two-Piece Retention Ramp.
- Platform Lights.
- Hand-Held Remote.
- Dual Pump, Power Down Option for reliable performance in cold weather.
- Trail Charger Kit provides a fully regulated 14-volt, 20-amp charge rate to remote liftgate batteries.
- Customized Options - contact factory.
- Galvanized Option.

Waltco Lift Corp.
Corporate Office United States
1777 Miller Parkway
Streetsboro, OH 44241
P: 330.633.9191
F: 330.633.1418

Waltco Sales
T: 800.211.3074
F: 800.211.3075
Email: sales@waltco.com

Waltco.com

