WDVBG

3,500 lb. and 4,500 lb. Capacities

SIMPLE TO MAINTAIN AND OPERATE, WITH AUTOMATIC SELF-LEVELING SYSTEM.

Optional Aluminum Platform Shown. Products shown may feature optional equipment. Content subject to change without notice.





STANDARD WDVBG SERIES ADVANTAGES INCLUDE:


- Lifetime warranty UHMW slide pads.
- Fold-down rear retention rails, designed specifically for bottled gas transportation.
- Power down.
- Hydraulic power open and close.
- Mechanical lock.
- Power unit preinstalled and tested in combination pump/battery box with pre-mounted hanger brackets.
- Standard steel platforms.
- Series Hydraulic Circuit Design and Automatic Self-Leveling System:
 - Load can be offset without compromising capacity
 - Platform always lifts parallel to truck bed, even on uneven road

surfaces

- Fully lubricated cylinders reduce seal wear and closed hydraulic system keeps out fluid contaminates
- Pre-mounted marine potted toggle switches with half rubber boot.
- LED lights.
- Thermally protected motors.
- Bottom stops for dock loading.
- Galvanized main frame.



WDVBG Series Gate in stowed position





WDVBG



1/2" Thick Heavy Duty Independent Bumper: Bumper that protects both the dock and the liftgate. Bumper pad is fixed while the trailer moves during dock loading. This prevents rubbing damage against dock. Bumper is independent of column. It takes the impact without damage to the column.

SPECIFICATIONS:

Bed Ht: 40"-57"

Model	Capacity	Platform	Ramp	Weight
WDBGG-35	3,500 lb.	36" x 82"	16" x 45"	2,316 lbs.
WDBGG-35	3,500 lb.	42" x 82"	16" x 45"	2,371 lbs.
WDBGG-45	4,500 lb.	36" x 82"	16" x 45"	2,316 lbs.
WDBGG-45	4,500 lb.	42" x 82"	16" x 45"	2,371 lbs.

Note: Platform increases to 88" with purchase of 102" wide vehicle option



UHMW Slide Pads: Lifetime warranty eliminates the cost of replacing rollers and downtime.

Pre-Mounted Marine Potted Toggle Switch: Protected against elements and pre-installed in a location that allows easy viewing of the platform work area.

Hands Free Positive Latching System: Mechanical design holds the platform secure and eliminates problems that occur with hydraulic/electric systems.

OPTIONAL EQUIPMENT:

- Dual controls adds a street side raise/lower control for driver convenience.
- Hand-held pendant control allows driver to operate the liftgate from ground or bed level.
- Gravity down on demand.
- Cab mounted power shut-off switch allows operator to shut-off power to liftgate control switch(s) to prevent unauthorized use of the liftgate.
- Platform materials:
 - Aluminum with aluminum rails
 - Galvanized steel
 - Bar grating
- Auxiliary hand-held backup switch and dual pump and motors.
- Batteries (Dual purpose, AGM, Deep cycle).
- Customized options contact factory.
- Single pump and motor box available (not batteries).

Waltco Lift Corp Corporate Office United States 1777 Miller Parkway Streetsboro, OH 44241 T: 330.633.9191 F: 330.633.1418 Waltco Sales T: 800.211.3074 F: 800.211.3075 Email: sales@waltco.com



Waltco.com