



PILE DRIVER (TRACE)

| Imperial | 8' | 10' | 8' (36" H) | 10' (36" H) | 12' |
|---|---|---|---|---|---|
| Moldboard Options | Steel | Steel | Steel | Steel | Steel |
| Blade Width | 8' | 10' | 8' | 10' | 12' |
| Blade Height | 30" | 30" | 36" | 36" | 42" |
| Side Plate Width | 56" | 56" | 56" | 56" | 56" |
| Side Plate Height | 30" | 30" | 36" | 36" | 42" |
| Moldboard Radius | 27" | 27" | 27" | 27" | 46" |
| Approx. Snow Capacity | 75 cu ft | 94 cu ft | 108 cu ft | 135 cu ft | 219 cu ft |
| Machine Application | Skid-Steer | Skid-Steer | Tractor / Wheel Loader | Tractor / Wheel Loader | Wheel Loader |
| Approx. Weight* | 2,127 lb | 2,249 lb | 2,221 lb | 2,377 lb | 2,644 lb |
| Cutting Edge Technology | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge |
| Cutting Edge Material | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts |
| Mount Type | Skid-Steer Attach Plate | Skid-Steer Attach Plate | Skid-Steer Attach Plate / Coupler | Skid-Steer Attach Plate / Coupler | Coupler |
| Skid-Steer Horsepower Compatibility | 30-50 hp | 30-50 hp | -- | -- | -- |
| Wheel Loader & Backhoe Horsepower Compatibility | -- | -- | 50-75 hp | 50-75 hp | 100-125 hp |
| Tractor Horsepower Compatibility | -- | -- | 50-100 hp | 50-100 hp | 75-150 hp |

| Metric | 8' | 10' | 8' (36" H) | 10' (36" H) | 12' |
|-------------------------|---|---|---|---|---|
| Models | 8' | 10' | 8' (36" H) | 10' (36" H) | 12' |
| Moldboard Options | Steel | Steel | Steel | Steel | Steel |
| Blade Width | 2.44 m | 3.05 m | 2.44 m | 3.05 m | 3.66 m |
| Blade Height | 76.2 cm | 76.2 cm | 91.44 cm | 91.44 cm | 106.68 cm |
| Side Plate Width | 142.24 cm | 142.24 cm | 142.24 cm | 142.24 cm | 142.24 cm |
| Side Plate Height | 76.2 cm | 76.2 cm | 91.44 cm | 91.44 cm | 106.68 cm |
| Moldboard Radius | 68.58 cm | 68.58 cm | 68.58 cm | 68.58 cm | 116.84 cm |
| Approx. Snow Capacity | 2.14 cu m | 2.68 cu m | 3.06 cu m | 3.82 cu m | 6.19 cu m |
| Machine Application | Skid-Steer | Skid-Steer | Tractor / Wheel Loader | Tractor / Wheel Loader | Wheel Loader |
| Approx. Weight* | 964.63 kg | 1,019.95 kg | 1,007.26 kg | 1,078.00 kg | 1,199.09 kg |
| Cutting Edge Technology | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge | TRACE -- Terrain Response Advanced Cutting Edge |



PILE DRIVER (TRACE)

| | | | | | |
|---|--|--|--|--|--|
| Cutting Edge Material | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts | High-Carbon Steel With Carbide Inserts |
| Mount Type | Skid-Steer Attach Plate | Skid-Steer Attach Plate | Skid-Steer Attach Plate / Coupler | Skid-Steer Attach Plate / Coupler | Coupler |
| Skid-Steer Horsepower Compatibility | 30-50 hp | 30-50 hp | -- | -- | -- |
| Wheel Loader & Backhoe Horsepower Compatibility | -- | -- | 50-75 hp | 50-75 hp | 100-125 hp |
| Tractor Horsepower Compatibility | -- | -- | 50-100 hp | 50-100 hp | 75-150 hp |

*Does not include vehicle mount weight.