



Striker™ (0.35 & 0.7 cu yd) Specifications

Technical Specifications

Imperial	0.7 cu yd	0.35 cu yd
Body Side Length	54"	30"
Capacity	0.7 cu yd	0.35 cu yd
Hopper Construction	16 ga SS	16 ga SS
Hopper Dimensions (LxWxH)	54" x 43" x 28"	30" x 38" x 26"
Overall Dimensions (LxWxH)	81" x 43" x 46"	57" x 38" x 46"
Min. Bed Length Required	44"	30"
Approx. Weight (Empty) Dual 12V DC Sealed Motors	420 lb	235 lb
Conveyor Width	15 ½"	11 ½"
Spinner Size	12"	12"
Spreading Width	Up to 30 ft	Up to 30 ft
Material	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix
Vehicle Application	1/2-Ton & Light Duty Pickup Trucks	UTVs & Compact Trucks

Metric	0.7 cu yd	0.35 cu yd
Body Side Length	1.37 m	0.76 m
Capacity	0.54 cu m	0.27 cu m
Hopper Construction	1.5 mm SS	1.5 mm SS
Hopper Dimensions (LxWxH)	137.16 cm x 109.22 cm x 71.12 cm	76.20 cm x 96.52 cm x 66.04 cm
Overall Dimensions (LxWxH)	205.74 cm x 109.22 cm x 116.84 cm	144.78 cm x 96.52 cm x 116.84 cm
Min. Bed Length Required	111.76 cm	76.20 cm
Approx. Weight (Empty) Dual 12V DC Sealed Motors	190.51 kg	106.59 kg
Conveyor Width	39.37 cm	29.21 cm
Spinner Size	30.48 cm	30.48 cm
Spreading Width	Up to 9.14 m	Up to 9.14 m
Material	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix
Vehicle Application	1/2-Ton & Light Duty Pickup Trucks	UTVs & Compact Trucks